

## **IGBT MODULE ( L series)**

## ■ Features

- High Speed Switching
  - Low Saturation Voltage
  - Voltage Drive
  - Isolated Package

## ■ Applications

- Ideal for Chopper Application
  - AC and DC Servo Drive Supply
  - Uninterruptible Power Supply
  - Industrial Machines, such as Welding Machines

### ■ Maximum Ratings and Characteristics

- Absolute Maximum Ratings

| Items                     |            | Symbols              | Ratings     | Units |
|---------------------------|------------|----------------------|-------------|-------|
| Collector-Emitter Voltage |            | V <sub>CES</sub>     | 600         | V     |
| Gate-Emitter Voltage      |            | V <sub>GFS</sub>     | ±20         | V     |
| Collector Current         | Continuous | I <sub>C</sub>       | 75          | A     |
|                           | 1ms        | I <sub>C</sub> pulse | 150         |       |
| Max. Power Dissipation    |            | P <sub>C</sub>       | 300         | W     |
| Operating Temperature     |            | T <sub>j</sub>       | +150        | °C    |
| Storage Temperature       |            | T <sub>stg</sub>     | -40 to +125 | °C    |
| Isolation Voltage         | AC. 1min.  | V <sub>is</sub>      | 2500        | V     |
| Screw Torque              |            | Mounting *1          | 1.7         | Nm    |
|                           |            | Terminals *1         | 1.7         |       |

- Electrical Characteristics ( $T_j=25^\circ\text{C}$  unless otherwise specified)


| Items                                | Symbols        | Test Conditions                            | Min. | Typ. | Max. | Units   |
|--------------------------------------|----------------|--|------|------|------|---------|
| Zero Gate Voltage Collector Current  | $I_{CES}$      | $V_{GE}=0V$ $V_{CE}=600V$ $T_c=25^\circ C$ |      |      | 1.0  | mA      |
| Gate-Emitter Leackage Current        | $I_{GES}$      | $V_{CE}=0V$ $V_{GE}=\pm 20V$               |      |      | 100  | nA      |
| Gate-Emitter Threshold Voltage       | $V_{GE}$ (th)  | $V_{CE}=20V$ $I_c=75mA$                    | 3.0  |      | 6.0  | V       |
| Collector-Emitter Saturation Voltage | $V_{CE}$ (sat) | $V_{GE}=15V$ $I_c=75A$                     |      | 2.7  | 3.5  | V       |
| Input Capacitance                    | $C_{iES}$      | $V_{GE}=0V$                                |      | 7100 |      | pF      |
| Output Capacitance                   | $C_{oES}$      | $V_{CE}=10V$                               |      | -    |      |         |
| Reverse Transfer Capacitance         | $C_{rES}$      | $f=1MHz$                                   |      | -    |      |         |
| Turn-on Time                         | $t_{on}$       | $V_{CC}=300V$                              |      | 0.4  | 0.8  | $\mu s$ |
|                                      | $t_r$          | $I_c=75A$                                  |      | 0.3  | 0.6  |         |
| Turn-off Time                        | $t_{off}$      | $V_{GE}=\pm 15V$                           |      | 0.6  | 1.0  |         |
|                                      | $t_f$          | $R_G=33\Omega$                             |      | 0.2  | 0.35 |         |

$t_{on}, t_f$ : Resistive Load       $t_{off}, t_f$ : Inductive Load


#### ● Thermal Characteristics

| Items              | Symbols               | Test Conditions       | Min. | Typ. | Max.  | Units |
|--------------------|-----------------------|-----------------------|------|------|-------|-------|
| Thermal Resistance | R <sub>th (j-c)</sub> | IGBT                  |      |      | 0.417 | °C/W  |
|                    |                       |                       |      |      |       |       |
|                    | R <sub>th (c-f)</sub> | With Thermal compound |      | 0.06 |       |       |

## ■ Outline Drawings



### ■ Equivalent Circuit Schematic



\*1 Recommendable Value  $1.3 \approx 1.7$  N·m (M4)