FUJI ELECTRIC

2MBI 300NB-060

2-Pack IGBT
600 V
300 A

IGBT MODULE (N series)

■ Features

- *Square RBSOA*
- *Low Saturation Voltage*
- *Less Total Power Dissipation*
- *Improved FWD Characteristic*
- *Minimized Internal Stray Inductance*
- *Overcurrent Limiting Function (~3 Times Rated Current)*

■ Applications

- *High Power Switching*
- *A.C. Motor Controls*
- *D.C. Motor Controls*
- *Uninterruptible Power Supply*

■ Outline Drawing



■ Maximum Ratings and Characteristics

• Absolute Maximum Ratings (T_c=25°C)

Items		Symbols	Ratings	Units
Collector-Emitter Voltage		V_{CES}	600	V
Gate -Emitter Voltage		V_{GES}	± 20	V
Collector Current	Continuous	I_C	300	A
	1ms	$I_{C\ PULSE}$	600	
	Continuous	$-I_C$	300	
	1ms	$-I_{C\ PULSE}$	600	
Max. Power Dissipation		P_C	1100	W
Operating Temperature		T_j	+150	°C
Storage Temperature		T_{stg}	-40 ~ +125	°C
Isolation Voltage	A.C. 1min.	V_{is}	2500	V
Screw Torque		Mounting *1	3.5	Nm
		Terminals *2	4.5	

Note: *1:Recommendable Value; 2.5 ~ 3.5 Nm (M5) or (M6)
*2:Recommendable Value; 3.5 ~ 4.5 Nm (M6)

■ Equivalent Circuit



• Electrical Characteristics (at T_j=25°C)

Items	Symbols	Test Conditions	Min.	Typ.	Max.	Units
Zero Gate Voltage Collector Current	I_{CES}	V_{GE}=0V V_{CE}=600V			2.0	mA
Gate-Emitter Leackage Current	I_{GES}	V_{CE}=0V V_{GE}=± 20V			30	µA
Gate-Emitter Threshold Voltage	$V_{GE(th)}$	V_{GE}=20V I_C=300mA	4.5		7.5	V
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	V_{GE}=15V I_C=300A			2.8	V
Input capacitance	C_{ies}	V_{GE}=0V		19800		pF
Output capacitance	C_{oes}	V_{CE}=10V		4400		
Reverse Transfer capacitance	C_{res}	f=1MHz		2000		
Turn-on Time	t_{ON}	V_{CC}=300V		0.6	1.2	µs
	t_r	I_C=300A		0.2	0.6	
Turn-off Time	t_{OFF}	V_{GE}=± 15V		0.6	1.0	
	t_f	R_G=6.8Ω		0.2	0.35	
Diode Forward On-Voltage	V_F	I_F=300A V_{GE}=0V			3.0	V
Reverse Recovery Time	t_{rr}	I_F=300A			300	ns

• Thermal Characteristics

Items	Symbols	Test Conditions	Min.	Typ.	Max.	Units
Thermal Resistance	$R_{th(j-c)}$	IGBT			0.11	°C/W
	$R_{th(j-c)}$	Diode			0.15	
	$R_{th(c-f)}$	With Thermal Compound		0.025		