

Medium Voltage Thyristor

Types K0349LC600 to K0349LC650

Old Type No.: P201CH60-65

Absolute Maximum Ratings

	VOLTAGE RATINGS	MAXIMUM LIMITS	UNITS
V_{DRM}	Repetitive peak off-state voltage, (note 1)	6000-6500	V
V_{DSM}	Non-repetitive peak off-state voltage, (note 1)	6000-6500	V
V_{RRM}	Repetitive peak reverse voltage, (note 1)	6000-6500	V
V_{RSM}	Non-repetitive peak reverse voltage, (note 1)	6100-6600	V

	OTHER RATINGS	MAXIMUM LIMITS	UNITS
$I_{T(AV)M}$	Maximum average on-state current, $T_{sink}=55^{\circ}\text{C}$, (note 2)	349	A
$I_{T(AV)M}$	Maximum average on-state current. $T_{sink}=85^{\circ}\text{C}$, (note 2)	221	A
$I_{T(AV)M}$	Maximum average on-state current. $T_{sink}=85^{\circ}\text{C}$, (note 3)	134	A
$I_{T(RMS)}$	Nominal RMS on-state current, $T_{sink}=25^{\circ}\text{C}$, (note 2)	705	A
$I_{T(d.c.)}$	D.C. on-state current, $T_{sink}=25^{\circ}\text{C}$, (note 4)	622	A
I_{TSM}	Peak non-repetitive surge $t_p=10\text{ms}$, $V_{RM}=0.6V_{RRM}$, (note 5)	4800	kA
I_{TSM2}	Peak non-repetitive surge $t_p=10\text{ms}$, $V_{RM} \leq 10\text{V}$, (note 5)	5300	kA
I^2t	I^2t capacity for fusing $t_p=10\text{ms}$, $V_{RM}=0.6V_{RRM}$, (note 5)	115×10^3	A^2s
I^2t	I^2t capacity for fusing $t_p=10\text{ms}$, $V_{RM} \leq 10\text{V}$, (note 5)	140×10^3	A^2s
$(di/dt)_{cr}$	Critical rate of rise of on-state current (repetitive), (Note 6)	150	$\text{A}/\mu\text{s}$
	Critical rate of rise of on-state current (non-repetitive), (Note 6)	300	$\text{A}/\mu\text{s}$
V_{RGM}	Peak reverse gate voltage	5	V
$P_{G(AV)}$	Mean forward gate power	2	W
P_{GM}	Peak forward gate power	30	W
V_{GD}	Non-trigger gate voltage, (Note 7)	0.25	V
$T_{j op}$	Operating temperature range	-40 to +115	$^{\circ}\text{C}$
T_{stg}	Storage temperature range	-40 to +150	$^{\circ}\text{C}$

Notes: -

- 1) De-rating factor of 0.13% per $^{\circ}\text{C}$ is applicable for T_j below 25°C .
- 2) Double side cooled, single phase; 50Hz, 180° half-sinewave.
- 3) Single side cooled, single phase; 50Hz, 180° half-sinewave.
- 4) Double side cooled.
- 5) Half-sinewave, 115°C T_j initial.
- 6) $V_D=67\%$ V_{DRM} , $I_{FG}=2\text{A}$, $t_f \leq 0.5\mu\text{s}$, $T_{case}=115^{\circ}\text{C}$.
- 7) Rated V_{DRM} .

Characteristics

	PARAMETER	MIN.	TYP.	MAX.	TEST CONDITIONS (Note 1)	UNITS
V_{TM}	Maximum peak on-state voltage	-	-	2.8	$I_{TM}=500A$	V
V_{TO}	Threshold voltage	-	-	1.568		V
r_T	Slope resistance	-	-	2.428		$m\Omega$
$(dv/dt)_{cr}$	Critical rate of rise of off-state voltage	1000	-	-	$V_D=80\% V_{DRM}$, linear ramp, Gate O/C	$V/\mu s$
I_{DRM}	Peak off-state current	-	-	50	Rated V_{DRM}	mA
I_{RRM}	Peak reverse current	-	-	50	Rated V_{RRM}	mA
V_{tr}	On-state recovery voltage	-	9.0	-	$I_T=3 \times I_{T(AV)M}$, $t_p=10ms$, $T_{case}=25^\circ C$	V
V_{GT}	Gate trigger voltage	-	-	3.0		V
I_{GT}	Gate trigger current	-	-	300	$T_j=25^\circ C$, $V_D=10V$, $I_T=3A$	mA
V_{GD}	Gate non-trigger voltage	-	-	0.25	Rated V_{DRM}	V
I_H	Holding current	-	-	1000	$T_j=25^\circ C$	mA
t_{gd}	Gate controlled turn-on delay time	-	0.6	1.2	$I_{FG}=2A$, $t_r=0.5\mu s$, $V_D=67\%V_{DRM}$, $I_{TM}=1000A$, $di/dt=10A/\mu s$, $T_j=25^\circ C$	μs
t_{gt}	Turn-on time	-	6.0	9.0		
Q_{rr}	Recovered Charge	-	3100	-		μC
Q_{ra}	Recovered Charge, 50% chord	-	2100	2500	$I_{TM}=1000A$, $t_p=1ms$, $di/dt=10A/\mu s$, $V_r=50V$	μC
I_{rm}	Reverse recovery current	-	130	-		
t_{rr}	Reverse recovery time, 50% chord	-	30	-		A
t_q	Turn-off time	-	800	-	$I_{TM}=1000A$, $t_p=1ms$, $di/dt=10A/\mu s$, $V_r=50V$, $V_{dr}=33\%V_{DRM}$, $dV_{dr}/dt=20V/\mu s$	μs
		-	1100	-	$I_{TM}=1000A$, $t_p=1ms$, $di/dt=10A/\mu s$, $V_r=50V$, $V_{dr}=33\%V_{DRM}$, $dV_{dr}/dt=200V/\mu s$	
R_{thJK}	Thermal resistance, junction to heatsink	-	-	0.047	Double side cooled	K/W
F	Mounting force	10	-	20		K/W
W_t	Weight	-	340	-		g

Notes: -

1) Unless otherwise indicated $T_j=115^\circ C$.

Notes on Ratings and Characteristics**1.0 Voltage Grade Table**

Voltage Grade	V_{DRM} V	V_{DSM} V	V_{RRM} V	V_{RSM} V	V_D DC V	V_R DC V
60	6000			6100	3000	
62	6200			6300	3100	
64	6400			6500	3200	
65	6500			6600	3250	

2.0 Extension of Voltage Grades

This report is applicable to other voltage grades when supply has been agreed by Sales/Production.

3.0 De-rating Factor

A blocking voltage de-rating factor of 0.13%/°C is applicable to this device for T_j below 25°C.

4.0 Repetitive dv/dt

Standard dv/dt is 1000V/μs.

5.0 Frequency Ratings

The curves illustrated in figures 17 & 18 are for guidance only and are superseded by the maximum ratings shown on page 1. For operation above line frequency, please consult the factory for assistance.

6.0 Snubber Components

When selecting snubber components, care must be taken not to use excessively large values of snubber capacitor or excessively small values of snubber resistor. Such excessive component values may lead to device damage due to the large resultant values of snubber discharge current. If required, please consult the factory for assistance.

7.0 Rate of rise of on-state current

The maximum un-primed rate of rise of on-state current must not exceed 400A/μs at any time during turn-on on a non-repetitive basis. For repetitive performance, the on-state rate of rise of current must not exceed 200A/μs at any time during turn-on. Note that these values of rate of rise of current apply to the total device current including that from any local snubber network.

8.0 Square wave frequency ratings


These ratings are given for load component rate of rise of on-state current of 50A/μs.

9.0 Duty cycle lines

The 100% duty cycle is represented on the frequency ratings by a straight line. Other duties can be included as parallel to the first.

10.0 Gate Drive

The nominal requirement for a typical gate drive is illustrated below. An open circuit voltage of at least 30V is assumed. This gate drive must be applied when using the full di/dt capability of the device.



The magnitude of I_{GM} should be between five and ten times I_{GT} , which is shown on page 2. Its duration (t_{p1}) should be 20 μ s or sufficient to allow the anode current to reach ten times I_L , whichever is greater. Otherwise, an increase in pulse current could be needed to supply the necessary charge to trigger. The 'back-porch' current I_G should remain flowing for the same duration as the anode current and have a magnitude in the order of 1.5 times I_{GT} .

11.0 Computer Modelling Parameters

11.1 Device Dissipation Calculations

$$I_{AV} = \frac{-V_{T0} + \sqrt{V_{T0}^2 + 4 \cdot ff \cdot r_T \cdot W_{AV}}}{2 \cdot ff \cdot r_T} \text{ and: } W_{AV} = \frac{\Delta T}{R_{th}}$$

$$\Delta T = T_{j\max} - T_{Hs}$$

Where $V_{T0}=1.568V$, $r_T=2.428m\Omega$,

R_{th} = Supplementary thermal impedance, see table below and

ff = Form factor, see table below.

Supplementary Thermal Impedance							
Conduction Angle	30°	60°	90°	120°	180°	270°	d.c.
Square wave Double Side Cooled	0.0509	0.0504	0.0499	0.0494	0.0485	0.0474	0.047
Square wave Single Side Cooled	0.0987	0.0981	0.0976	0.0972	0.0963	0.0952	0.094
Sine wave Double Side Cooled	0.0505	0.0498	0.0493	0.0489	0.0475		
Sine wave Single Side Cooled	0.0983	0.0976	0.0971	0.0966	0.0953		

Form Factors							
Conduction Angle	30°	60°	90°	120°	180°	270°	d.c.
Square wave	3.464	2.449	2	1.732	1.414	1.149	1
Sine wave	3.98	2.778	2.22	1.879	1.57		

11.2 Calculating V_T using ABCD Coefficients

The on-state characteristic I_T vs. V_T , on page 6 is represented in two ways;

- (i) the well established V_{T0} and r_T tangent used for rating purposes and
- (ii) a set of constants A, B, C, D, forming the coefficients of the representative equation for V_T in terms of I_T given below:

$$V_T = A + B \cdot \ln(I_T) + C \cdot I_T + D \cdot \sqrt{I_T}$$

The constants, derived by curve fitting software, are given below for both hot and cold characteristics. The resulting values for V_T agree with the true device characteristic over a current range, which is limited to that plotted.

25°C Coefficients		115°C Coefficients	
A	0.2103143	A	-0.8731799
B	0.4754865	B	0.650089
C	2.581886×10^{-3}	C	3.072624×10^{-3}
D	-0.09062255	D	-0.08511282

11.3 D.C. Thermal Impedance Calculation

$$r_t = \sum_{p=1}^{p=n} r_p \cdot \left(1 - e^{\frac{-t}{\tau_p}} \right)$$

Where $p = 1$ to n , n is the number of terms in the series and:

t = Duration of heating pulse in seconds.

r_t = Thermal resistance at time t .

r_p = Amplitude of p_{th} term.

τ_p = Time Constant of r_{th} term.

The coefficients for this device are shown in the tables below:

D.C. Double Side Cooled				
Term	1	2	3	4
r_p	0.02328162	0.0165603	4.739431×10^{-3}	1.805256×10^{-3}
τ_p	0.7294482	0.1571701	0.0343812	0.01059348

D.C. Single Side Cooled				
Term	1	2	3	4
r_p	0.06051172	0.0215729	9.551987×10^{-3}	2.562011×10^{-3}
τ_p	5.722131	0.3167688	0.06285918	0.01198397

Curves

Figure 1 – On-state characteristics of Limit device




Figure 2 - Transient Thermal Impedance




Figure 3 – Gate Characteristics - Trigger Limits




Figure 4 - Gate Characteristics - Power Curves








Figure 5 – Recovered Charge, Q_{rr} Figure 6 – Recovered charge, Q_{ra} (50% chord)Figure 7 – Reverse recovery current, I_{rm} Figure 8 – Reverse recovery time, t_{rr} 

Figure 9 – On-state current vs. Power dissipation – Double Side Cooled (Sine wave)




Figure 10 – On-state current vs. Heatsink temperature - Double Side Cooled (Sine wave)




Figure 11 – On-state current vs. Power dissipation – Double Side Cooled (Square wave)




Figure 12 – On-state current vs. Heatsink temperature – Double Side Cooled (Square wave)




Figure 13 – On-state current vs. Power dissipation
– Single Side Cooled (Sine wave)




Figure 15 – On-state current vs. Power dissipation
– Single Side Cooled (Square wave)




Figure 14 – On-state current vs. Heatsink temperature – Single Side Cooled (Sine wave)




Figure 16 – On-state current vs. Heatsink temperature – Single Side Cooled (Square wave)




Figure 17 – Square Wave Frequency Ratings






Figure 18 – Sine Wave Frequency Ratings

Figure 17 – Maximum surge and I^2t Ratings

Outline Drawing & Ordering Information