


**POW-R-BLOK™**  
**Dual Diode Isolated Module**  
**350 Amperes & Up to 1700 Volts**



**ND41\_\_35**  
**Dual Diode Isolated**  
**POW-R-BLOK™ Module**  
**350 Amperes / 600-1700 Volts**

**Description:**

Powerex Dual Diode Modules are designed for use in applications requiring rectification and isolated packaging. The modules are isolated for easy mounting with other components on a common heatsink. POW-R-BLOK™ has been tested and recognized by the Underwriters Laboratories.

**Features:**

- Electrically Isolated Heatsinking
- Aluminum Nitride Isolator
- Compression Bonded Elements
- Metal Baseplate
- Low Thermal Impedance for Improved Current Capability
- UL Recognized

**Benefits:**

- No Additional Insulation Components Required
- Easy Installation
- No Clamping Components Required
- Reduce Engineering Time

**Applications:**

- Bridge Circuits
- AC & DC Motor Drives
- Battery Supplies
- Power Supplies
- Large IGBT Circuit Front Ends

**ND41 Outline Dimensions**

Dimension	Inches	Millimeters
A	4.57	116
B	3.66	93
C	3.15	80.0
E	2.06	52.3
F	2.05	52.0
G	1.97	50.0
H	1.90	48.3
J	1.50	38.1
K	1.38	35.0
L	1.35	34.3
M	1.122	28.5
N	.71	18.0
P	.57	14.5
Q	.625	15.9
R	.394	10.00
S	.350	8.9
T	M8 Metric	M8
U	.22 Dia.	5.6 Dia.
W	.12	3.0

Note: Dimensions are for reference only.

**Ordering Information:**

Select the complete eight digit module part number from the table below.

Example: ND411735 is a 1700Volt, 350 Ampere Dual Diode Isolated POW-R-BLOK™ Module

Type	Voltage Volts (x100)	Current Amperes (x10)
ND41	06	35
	08	
	10	
	12	
	14	
	16	
	17	

**Absolute Maximum Ratings**

Characteristics	Conditions	Symbol		Units
Repetitive Peak Reverse Blocking Voltage		$V_{RRM}$	up to 1700	V
Non-Repetitive Peak Reverse Blocking Voltage ( $t < 5$ msec)		$V_{RSM}$	$V_{RRM} + 100$	V
RMS Forward Current	180° Conduction, $T_C=102^\circ\text{C}$	$I_{F(RMS)}$	550	A
	180° Conduction, $T_C=108^\circ\text{C}$	$I_{F(RMS)}$	510	A
	180° Conduction, $T_C=112^\circ\text{C}$	$I_{F(RMS)}$	470	A
Average Forward Current	180° Conduction, $T_C=102^\circ\text{C}$	$I_{F(AV)}$	350	A
	180° Conduction, $T_C=108^\circ\text{C}$	$I_{F(AV)}$	325	A
	180° Conduction, $T_C=112^\circ\text{C}$	$I_{F(AV)}$	300	A
Peak One Cycle Surge Current, Non-Repetitive Initial $T_j = T_j$ max	60 Hz, 100% $V_{RRM}$ reapplied	$I_{FSM}$	8450	A
	60 Hz, No $V_{RRM}$ reapplied	$I_{FSM}$	12,500	A
	50 Hz, 100% $V_{RRM}$ reapplied	$I_{FSM}$	7340	A
	50 Hz, No $V_{RRM}$ reapplied	$I_{FSM}$	11,000	A
Peak One Cycle Surge Current, Non-Repetitive Initial $T_j = 25\text{C}$	60 Hz, 100% $V_{RRM}$ reapplied	$I_{FSM}$	9970	A
	60 Hz, No $V_{RRM}$ reapplied	$I_{FSM}$	14,750	A
	50 Hz, 100% $V_{RRM}$ reapplied	$I_{FSM}$	8670	A
	50 Hz, No $V_{RRM}$ reapplied	$I_{FSM}$	13,000	A
Peak Three Cycle Surge Current, Non-Repetitive Initial $T_j = T_j$ max	60 Hz, 100% $V_{RRM}$ reapplied	$I_{FSM}$	6760	A
Peak Ten Cycle Surge Current, Non-Repetitive Initial $T_j = T_j$ max	60 Hz, 100% $V_{RRM}$ reapplied	$I_{FSM}$	5330	A
$I^2t$ for Fusing for One Cycle, 8.3 milliseconds No $V_{RRM}$ reapplied	Initial $T_j = T_j$ max	$I^2t$	651,000	$\text{A}^2 \text{ sec}$
	Initial $T_j = 25\text{C}$	$I^2t$	906,000	$\text{A}^2 \text{ sec}$
Operating Temperature		$T_j$	-40 to +150	$^\circ\text{C}$
Storage Temperature		$T_{stg}$	-40 to +150	$^\circ\text{C}$
Max. Mounting Torque, M6 Mounting Screw			45	in.-Lb.
			5	Nm
Max. Mounting Torque, M8 Terminal Screw			95	in.-Lb.
			11	Nm
Module Weight, Typical			840	g
			1.85	lb.
V Isolation @ 25C	60 seconds	$V_{rms}$	3000	V
	1 second	$V_{rms}$	3600	V

**Electrical Characteristics, T<sub>J</sub>=25°C unless otherwise specified**


Characteristics	Symbol	Test Conditions	Min.	Max.	Units
Repetitive Peak Reverse Leakage Current	I <sub>RRM</sub>	Up to 1700V, T <sub>J</sub> =150°C		30	mA
Peak On-State Voltage	V <sub>FM</sub>	I <sub>FM</sub> =1000A		1.20	V
Threshold Voltage, Low-level	V <sub>(TO)1</sub>	T <sub>J</sub> = 150°C, I = 15%I <sub>F(AV)</sub> to πI <sub>F(AV)</sub>		0.654	V
Slope Resistance, Low-level	r <sub>T1</sub>			0.320	mΩ
Threshold Voltage, High-level	V <sub>(TO)2</sub>	T <sub>J</sub> = 150°C, I = πI <sub>F(AV)</sub> to I <sub>FSM</sub>		0.726	V
Slope Resistance, High-level	r <sub>T2</sub>			0.272	mΩ
V <sub>TM</sub> Coefficients, Full Range		T <sub>J</sub> = 150°C, I = 15%I <sub>F(AV)</sub> to I <sub>FSM</sub> V <sub>FM</sub> = A + B Ln I + C I + D Sqrt I	A = B = C = D =	0.7304 -0.0314 2.15 E-4 7.74 E-3	
Diode Reverse Recovery Time (Typical)	t <sub>rr</sub>	I <sub>fm</sub> = 1500A, T <sub>p</sub> = 190 μs di/dt = -25A/μs		10	μs

**Thermal Characteristics**


Characteristics	Symbol		Max.	Units
Thermal Resistance, Junction to Case	R <sub>ΘJ-C</sub>	Per Module, both conducting Per Junction both conducting	0.07 0.14	°C/W °C/W
Thermal Impedance Coefficients	Z <sub>ΘJ-C</sub>	Z <sub>ΘJ-C</sub> = K <sub>1</sub> (1-exp(-t/τ <sub>1</sub> )) + K <sub>2</sub> (1-exp(-t/τ <sub>2</sub> )) + K <sub>3</sub> (1-exp(-t/τ <sub>3</sub> )) + K <sub>4</sub> (1-exp(-t/τ <sub>4</sub> ))	K <sub>1</sub> = 5.27E-3 K <sub>2</sub> = 1.17E-2 K <sub>3</sub> = 5.26E-2 K <sub>4</sub> = 6.97E-2	τ <sub>1</sub> = 1.69E-4 τ <sub>2</sub> = 2.07E-2 τ <sub>3</sub> = 2.37E-1 τ <sub>4</sub> = 2.46
Thermal Resistance, Case to Sink Lubricated	R <sub>ΘC-S</sub>	Per Module	0.03	°C/W

## POW-R-BLOK™ Dual Diode Isolated Module 350 Amperes & Up to 1700 Volts


Typical On-State Forward Voltage Drop  
(T<sub>j</sub> = 150C)




Maximum Transient Thermal Impedance  
(Junction To Case)




Maximum On-State Power Dissipation  
(Sinusoidal Waveform)



Maximum Allowable Case Temperature  
(Sinusoidal Waveform)



Maximum On-State Power Dissipation  
(Rectangular Waveform)



Maximum Allowable Case Temperature  
(Rectangular Waveform)

