

TOSHIBA Photocoupler GaAlAs IRED + Photo IC

P701

Industrial inverters

Inverter for air conditioners

IGBT/Power MOS FET gate drive

P701 consists of a GaAlAs light-emitting diode and an integrated photodetector.

This unit is 6-lead SDIP package. The P701 is 50% smaller than the 8-pin DIP and meets the reinforced insulation class requirements of international safety standards. Therefore the mounting area can be reduced in equipment requiring safety standard certification.

The P701 is suitable for gate driving circuits for IGBTs or power MOSFETs. In particular, the P701 is capable of "direct" gate driving of low-power IGBTs.

- Peak output current : ± 0.6 A (max)
- Guaranteed performance over temperature : -40 to 100°C
- Supply current : 2 mA (max)
- Power supply voltage : 10 to 30 V
- Threshold input current : $I_{FLH} = 5$ mA (max)
- Switching time (t_{pLH} / t_{pHL}) : 700 ns (max)
- Common mode transient immunity : ± 10 kV/μs (min)
- Isolation voltage : 5000 Vrms (min)
- Construction mechanical rating


	7.62-mm pitch standard type	10.16-mm pitch TLPXXXF type
Creepage Distance	7.0 mm (min)	8.0 mm (min)
Clearance	7.0 mm (min)	8.0 mm (min)
Insulation Thickness	0.4 mm (min)	0.4 mm (min)

- UL Recognized : UL1577, File No. E67349
- Option (D4)
TÜV approved : EN60747-5-2
Certificate No. R50033433
Maximum operating insulation voltage : 890 Vpk
Highest permissible over voltage : 8000 Vpk

(Note) When a EN60747-5-2 approved type is needed,
please designate the "Option(D4)"


Truth Table

Input	LED	Tr1	Tr2	Output
H	ON	ON	OFF	H
L	OFF	OFF	ON	L




Weight : 0.26 g (typ.)

Pin Configuration (Top View)



Schematic



A 0.1- μ F bypass capacitor must be connected between pins 6 and 4. (See Note 6.)

Maximum Ratings (Ta = 25 °C)

Characteristics		Symbol	Rating	Unit
LED	Forward current	I _F	20	mA
	Forward current derating (Ta ≥ 85°C)	ΔI _F /ΔTa	-0.54	mA/°C
	Peak transient forward current (Note 1)	I _{FP}	1	A
	Reverse voltage	V _R	5	V
	Junction temperature	T _j	125	°C
Detector	"H" peak output current (Note 2)	I _{OPH}	-0.6	A
	"L" peak output current (Note 2)	I _{OPL}	0.6	A
	Output voltage	V _O	35	V
	Supply voltage	V _{CC}	35	V
	Junction temperature	T _j	125	°C
Operating frequency (Note 3)		f	25	kHz
Operating temperature range		T _{opr}	-40 to 100	°C
Storage temperature range		T _{stg}	-55 to 125	°C
Lead soldering temperature (10 s) (Note 4)		T _{sol}	260	°C
Isolation voltage (AC, 1 minute, R.H. ≤ 60%) (Note 5)		BV _S	5000	Vrms

Note 1: Pulse width P_W ≤ 1 μs, 300 pps

Note 2: Exponential waveform pulse width P_W ≤ 2 μs, f ≤ 15 kHz

Note 3: Exponential waveform I_{OPH} ≤ -0.3 A (≤ 2 μs), I_{OPL} ≤ +0.3 A (≤ 2 μs), Ta = 100 °C

Note 4: For the effective lead soldering area

Note 5: Device considered a two-terminal device: pins 1, 2 and 3 paired with pins 4, 5 and 6 respectively.

Note 6: A ceramic capacitor (0.1 μF) should be connected from pin 6 to pin 4 to stabilize the operation of the high gain linear amplifier. Failure to provide the bypassing may impair the switching property.

The total lead length between capacitor and coupler should not exceed 1 cm.

Recommended Operating Conditions

Characteristics	Symbol	Min	Typ.	Max	Unit
Input current, ON (Note 7)	I _F (ON)	7.5	—	10	mA
Input voltage, OFF	V _F (OFF)	0	—	0.8	V
Supply voltage	V _{CC}	10	—	30	V
Peak output current	I _{OPH} / I _{OPL}	—	—	± 0.2	A
Operating temperature	T _{opr}	-40	—	100	°C

Note 7: Input signal rise time (fall time) < 0.5 μs.

Electrical Characteristics (Ta = -40 to 100 °C, unless otherwise specified)

Characteristics	Symbol	Test Circuit	Test Condition		Min	Typ.*	Max	Unit
Forward voltage	V _F	—	I _F = 5 mA, Ta = 25 °C		—	1.55	1.70	V
Temperature coefficient of forward voltage	ΔV _F /ΔTa	—	I _F = 5 mA		—	-2.0	—	mV/°C
Input reverse current	I _R	—	V _R = 5 V, Ta = 25 °C		—	—	10	μA
Input capacitance	C _T	—	V = 0 V, f = 1 MHz, Ta = 25 °C		—	45	—	pF
Output current (Note 8)	"H" Level	I _{OPH1}	1	V _{CC} = 15 V I _F = 5 mA	V ₆₋₅ = 4 V	-0.2	-0.38	—
		I _{OPH2}			V ₆₋₅ = 10 V	-0.4	-0.60	—
	"L" Level	I _{OPL1}	2	V _{CC} = 15 V I _F = 0 mA	V ₅₋₄ = 2 V	0.2	0.36	—
		I _{OPL2}			V ₅₋₄ = 10 V	0.4	0.62	—
Output voltage	"H" Level	V _{OH}	3	V _{CC} = 10 V	I _O = -100 mA, I _F = 5 mA	6.0	8.5	—
	"L" Level	V _{OL}	4		I _O = 100 mA, V _F = 0.8 V	—	0.4	1.0
Supply current	"H" Level	I _{CCH}	5	V _{CC} = 10 to 30 V V _O =Open	I _F = 10 mA	—	1.4	2.0
	"L" Level	I _{CCL}	6		I _F = 0 mA	—	1.3	2.0
Threshold input current	L → H	I _{FLH}	—	V _{CC} = 15 V, V _O > 1 V		—	2.5	5 mA
Threshold input voltage	H → L	V _{FHL}	—	V _{CC} = 15 V, V _O < 1 V		0.8	—	— V
Supply voltage	V _{CC}	—	—	—	—	10	—	30 V

(*): All typical values are at Ta = 25°C

Note 8: Duration of I_O time ≤ 50 μs, 1 pulse

Note 9: This product is more sensitive than conventional products to electrostatic discharge (ESD) owing to its low power consumption design.

It is therefore all the more necessary to observe general precautions regarding ESD when handling this component.







Isolation Characteristics (Ta = 25 °C)





Characteristic	Symbol	Test Condition		Min.	Typ.	Max.	Unit
Capacitance input to output	C _S	V = 0 V, f = 1MHz (Note 5)		—	1.0	—	pF
Isolation resistance	R _S	R.H. ≤ 60 %, V _S = 500 V (Note 5)		1×10 ¹²	10 ¹⁴	—	Ω
Isolation voltage	BVs	AC, 1 minute		5000	—	—	V _{rms}
		AC, 1 second, in oil		—	10000	—	
		DC, 1 minute, in oil		—	10000	—	V _{dc}

Switching Characteristics ($T_a = -40$ to 100 °C, unless otherwise specified)

Characteristics		Symbol	Test Circuit	Test Condition		Min	Typ.*	Max	Unit
Propagation delay time L → H		t_{PLH}	7	$V_{CC} = 30$ V $R_g = 47 \Omega$ $C_g = 3$ nF		$I_F = 0 \rightarrow 5$ mA	100	—	700
		t_{PHL}				$I_F = 5 \rightarrow 0$ mA	100	—	700
Output rise time (10–90 %)		t_r				$I_F = 0 \rightarrow 5$ mA	—	50	—
		t_f				$I_F = 5 \rightarrow 0$ mA	—	50	—
Switching time dispersion between ON and OFF		$ t_{PHL}-t_{PLH} $	8	$V_{CM} = 1000$ Vp-p $V_{CC} = 30$ V $T_a = 25$ °C		$I_F = 0, 5$ mA	-500	—	500
Common mode transient immunity at HIGH level output		CM_H				$I_F = 5$ mA V_O (min) = 26 V	-10000	—	—
Common mode transient immunity at LOW level output		CM_L	8			$I_F = 0$ mA V_O (max) = 1 V	10000	—	—

(*): All typical values are at $T_a = 25$ °C.







Test Circuit 1: I_{OPH} Test Circuit 2: I_{OPL} Test Circuit 3: V_{OH} Test Circuit 4: V_{OL} Test Circuit 5: I_{CCH} Test Circuit 6: I_{CCL} 

Test Circuit 7: t_{PLH} , t_{PHL} , t_r , t_f , PDD**Test Circuit 8: CM_H , CM_L** 






$$CM_L = \frac{800 \text{ V}}{t_r (\mu\text{s})}$$

$$CM_H = - \frac{800 \text{ V}}{t_f (\mu\text{s})}$$

CM_L (CM_H) is the maximum rate of rise (fall) of the common mode voltage that can be sustained with the output voltage in the LOW (HIGH) state.

$I_F - V_F$  $V_F / Ta - I_F$  $I_F - Ta$  $I_{FLH} - Ta$  $V_{OL} - Ta$  $V_{OH} - Ta$ 

*: The above graphs show typical characteristics.



*: The above graphs show typical characteristics.